

## 2- and 3-Year Maintenance-Free CO or H<sub>2</sub>S Detectors



The UNI 321 is a disposable or maintenance-free version of UNI single gas detector. It detects hydrogen sulfide (H<sub>2</sub>S) or carbon monoxide (CO) in a selection of models with operating lives of 24 months (MP102) or 36 months (MP103). The detectors have large LCDs providing maximum readability in the field. Six bright red LEDs allow for quick alarm notification. Constructed of strong and durable material, the UNI 321 is designed to be comfortable, yet drop-resistant. The UNI detectors can easily be bump tested and calibrated using the CaliCase System.

### Features, Functions and Benefits

- Simple GO, NO-GO!
- No Maintenance needed for life of instrument (except when used under extreme conditions)
- Low cost of ownership
- Large Display
- Durable Housing
- Solid stainless-steel Alligator Clip
- 50% larger single-cell Battery
- Daily functional Self-Test
- 50 Event Datalogging
- Docking Station for calibration and event download
- UL Classification Class 123, Groups ABCDEFG





**UNI Docking Box**



**CaliCase Docking Station**

## Detector Specifications

<b>Size</b>	3.46 x 2.44 x 1.3 in
<b>Weight</b>	4.4 oz (125 g)
<b>Temperature</b>	-4°F to 122°F (-20°C to 50°C)
<b>Humidity</b>	5 to 95% relative humidity (non-condensing)
<b>Alarm type</b>	<ul style="list-style-type: none"> <li>• High &amp; Low alarms</li> <li>• Over range alarm</li> <li>• Low battery alarm</li> </ul>
<b>Alarm signal</b>	<ul style="list-style-type: none"> <li>• 95 dB @ 30 cm</li> <li>• Bright red LEDs</li> <li>• Built in vibrator</li> </ul>
<b>Calibration</b>	Manual zero (CaliCase/MP300T1 allows 2-point calibration, zero and span)
<b>Event log</b>	Up to 50 alarm events
<b>Response time (t90)</b>	15 seconds
<b>IP rating</b>	IP-67
<b>EMI/RFI</b>	EMC directive: 2014/30/EU
<b>Safety Certifications</b>	<p>  Class I, Div 1, Group ABCD            Class II, Div 1, Group EFG            Class III, Div 1            T4, -20°C ≤ T<sub>amb</sub> ≤ +50°C         </p> <p> <b>IECEX</b> Ex ia IIC T4 Ga         </p> <p> <b>ATEX</b>  II 1G            Ex ia IIC T4 Ga         </p>
<b>Operating life</b>	<ul style="list-style-type: none"> <li>• 2 years for MP102</li> <li>• 3 years for MP103</li> </ul>

## Model Options

Gas	Range	Model	P/N
<b>H<sub>2</sub>S (Hydrogen Sulfide)</b>	0.1 – 100 ppm	MP102	M015-0002-000
		MP103	M016-0002-000
<b>CO (Carbon Monoxide)</b>	1 – 500 ppm	MP102	M015-0001-000
		MP103	M016-0001-000

**Distributed By:**

\* Due to ongoing research and product improvement, specifications are subject to change without notice \*